## Accelerated Testing


## Requirement for a Valid Test


Must exercise same failure mechanisms as those found under operational conditions


#### NO EXCEPTIONS!!!


## Extrapolation

- Failure Model
  - Must be equally valid at stress and at use conditions
- Stress Conditions limited by physics of the faiture process
  - Oversteening









#### Arrhenius

- Most actual failure mechanisms are not purely Arrhenius
  - Often complex with other temperature dependencies besides thermal activation
- Most, however, do have an Arrhenius component
  - Usually associated with a mass transport mechanism

#### Extrapolation

$$Rate = A \exp\left(\frac{-\Delta H}{kT}\right)$$


- Arrhenius Relation
- Thermally Activated
- $\Delta H$  is the activation energy
  - Depends on the Failure Mechanism
  - Usually the Transport Mechanism (Diffusion)

#### Extrapolation

#### **Acceleration Factor**

- Relates time at stress to time in the field
- Depends on Failure Mechanism
- Requires Failure Model
  - Electromigration
  - Stress Voiding
  - Hot Carrier Degradation
  - TDDB
  - Corrosion

## Bathtub Curve Experimental



#### Corollary

## Everything is Wearout

Defects make the Difference

## Accelerated Testing

- Implicit in the concept of accelerated testing is the assumption that there is a valid physical model that relates failure at the accelerated test conditions to operational use conditions
- Empirical Models are dangerous and cannot be recommended
  - Only good for interpolation not extrapolation

#### Extrapolation

- Use Conditions (Typical)
  - Temperature
    - 50 to 125C
  - Voltages
    - 5 Volts to 1.5 Volts
  - Current Density
    - Up to 5 x 105 Amps/cm<sup>2</sup>

#### Extrapolation

- Acceleration
  - Reduce failure times to experimentally convenient levels.
    - Hours as opposed to years
  - Accomplished by operating outside of typical use parameters
    - Depends on failure mechanism

# Kendall and Stuart The Advanced Theory of Statistics

"A statistical relationship, however strong and however suggestive, can never establish a causal connection. Our ideas on causation must come from outside statistics, ultimately from some theory"

#### Max Born

"The concept of chance enters into the very first steps of scientific activity, by virtue of the fact that no observation is absolutely correct.....whether a concrete case of a cause-effect relationship exists can only be judged by applying the laws of chance to the observation"

## Why Accelerated Testing?

- Product lifetime in years
  - -100,000 hours at 85C
  - 10 Years at 100C
  - 5 years at 125C
- Development time in months
  - 18 to 24 months typical time to market for microprocessor

## Challenges

- Extrapolation
  - Obtain Data in a short time (weeks)
  - Extrapolated to 10 years or more in lifetime
- Scaling
  - Test structure is small and simple
  - Product chip is large and complicated

- Through Qualification
  - Qualification Testing
    - Lifetime Predictions
    - Qualification Criteria
  - Design Verification
    - Designers
    - Product Engineers
  - Reproducibility
    - · Yield
    - Process Engineering

- Through Generation of Design Rules
  - Reliability Testing
  - Process Engineering
    - Yield
    - Capability
  - Marketing Requirements
    - Performance
    - Reliability

#### Failure Mechanisms

- Electromigration
  - Temperature, Current Density
- Stress Voiding
  - Temperature
- Hot Carrier, TDDB
  - Temperature, Voltage, Frequency
- Corrosion
  - Temperature, Humidity, Cycling
- · Thermal Fatigue, Soret Effect
  - $-\Delta T$ , Cycle Frequency

#### Modes vs. Mechanisms

• If we can test failure mechanisms and understand the relationship, we do not need to reproduce the failure mode.

• Requires detailed understanding of the failure process and materials science

- Failure Mechanism
  - The physical process that leads to failure
    - Electromigration
    - TDDB
    - Hot Carrier Degradation
    - Corrosion
    - Thermal Fatigue
    - Alpha Particle
    - ESD

- Failure Mode
  - How the failure manifests itself
    - Functional Failures
    - Speed Shifts
    - Doesn't conduct electricity
      - Open Circuit
    - Conducts too much electricity
      - short circuit
      - leakage
    - Errors

#### Definitions and Distinctions

#### • MTF

- Light bulbs will fail after approximately 1000 hours
- Throw it away

#### MTBF

- The average lamp will fail after 1000 hours
- Many light bulbs of various ages
- replace the light bulb

## MTF and MTBF

- MTF is NOT a function of time
  - Characteristic of the failure distribution
  - MTF IS a time
- MTBF can be a function of time.
  - For a system composed of identical parts with a defined MTF, the MTBF will decrease as a function of time

#### Definitions and Distinctions


- MTF
  - Median Time to Failure
    - Component Failure
    - Non-Repairable
    - Wear-out
- MTBF
  - Mean Time Between Failures
    - Repairable Systems
    - Maintenance Schedule

#### Definitions and Distinctions

- FITs
  - "Failures In Time"
- Failures in 109 device hours
  - can be misleading
  - must be used properly

1 million devices for 10 hours does NOT equal 10 devices for 1 million hours

#### Bathtub Curve



- Reliability requires the input of more than just the reliability engineer
  - Design
  - Reliability Testing
  - Manufacturing
  - Process Engineering
  - Product Engineering
    - Yield Engineering
  - Marketing

- Definition
  - Definitions and Standards Committee of the IEEE

"The ability of an item to perform a required function under stated conditions for a stated period of time"

- James R. Schlesinger
  - Former US Secretary of Defense

"Reliability is, after all, engineering in its most practical form"